

## ADE-FIX

### QUICK-SETTING ACRYLIC ASSEMBLY ADHESIVE

Quick-setting acrylic assembly adhesive, ideal for securing skirting boards, wooden profiles, polystyrene and plaster panels. Can also be used on plastic and metal materials (excluding PE, PP, PTFE). Keep in a dry place away from heat sources.

### TECHNICAL CHARACTERISTICS:

- Quick-setting monocomponent
- Suction effect
- Ideal for bonding skirting boards

### WHERE IT CAN BE APPLIED:

- Wood or PVC edging or skirting boards on absorbent surfaces
- Plaster or polystyrene decorative elements on absorbent surfaces
- Metal profiles on absorbent surfaces
- For bondings that are not permanently exposed to moisture

### SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Clear paste
Yield: (g/m <sup>2</sup> ):	10-12 linear metres for a piped line (with a 6 mm diameter) (the product yield may vary depending on the porosity of the surface)
Usage temperature (°C):	+5 - +30
Open time (minutes):	10 - 15
Ready for walking on (minutes):	about 120 hours, depending on the environmental conditions
Final setting (hours):	after 18 - 24 (ready-to-walk-on and final setting times vary depending on weather conditions and the thickness of the layer applied)
Application/Equipment:	Caulking gun - 280/310 ml
Equipment cleaning:	water, before the product sets
Product removal:	GR7 Solvent
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	310 ml Cartridges
Usage limitations:	Before use, the product should be brought to a temperature of at least 15°C. Apply when the relative air humidity is between 40% and 70%. Always use suitable personal protective equipment Always consult the technical and safety information sheets

### SURFACE PREPARATION:

Check that the surface to be bonded is dry, clean, free from loose parts and not liable to continual rising damp.

### APPLICATION:

The product is ready for use. Insert the 310 ml tube into its applicator. Carefully cut one end of the cartridge and after attaching the special nozzle, apply the adhesive directly to one of the two surfaces in small dots or a continuous piped line.

Thoroughly press the product onto the surface so the space underneath is completely filled with adhesive.

Remove any glue residue with a cloth before the product has set, and in any case, before 5 minutes have elapsed. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

### HAZARD PICTOGRAMS:

--                      --                      --