



ADEPROMOT-SPECIAL

CONSOLIDATING, DUST-REPELLENT ADHESION PROMOTER

Water-dispersed primer with silanised resin base, suitable for absorbent surfaces or **non-absorbent floors** (ceramic, natural stone, wooden floors, vinyl glue residues), before applying concrete-based skim-coats or self-levellers. ADEPROMOT-SPECIAL can also be used on concrete screeds as a dust-repellent before bonding with our bicomponent or silane adhesives.

TECHNICAL CHARACTERISTICS:

- Monocomponent
- Water-based
- Easy to apply
- Suitable as a primer for bicomponent or silane adhesives

WHERE IT CAN BE APPLIED:

- Traditional concrete screeds
- Anhydrite screeds (calcium sulphate)
- Properly sanded wood or ceramic floors

DO NOT USE:

- On surfaces subject to continual rising damp that are not protected by a vapour seal barrier.

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Light blue liquid
Viscosity, Ford 4 at 20 °C (seconds):	11 - 13
Dry (%):	34 - 37
Yield: (g/m ²):	100 - 200
Working life (minutes):	5 - 20
Usage temperature (°C):	+15 - +25
Time before use (days):	1 - 3
Application/Equipment:	Roller, brush
Equipment cleaning:	Water, before the product sets
Storage (months): maximum temperature +5 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	10 kg containers
Recommendations for use:	Do not apply in damp environments Frost sensitive Always use suitable personal protective equipment Always consult the technical and safety information sheets Allow the product to reach 20 °C before applying

SURFACE PREPARATION:

Always use suitable tools to check the moisture content in the sub-floor. The sub-floor must be compact, free from moisture and with loose parts, such as chalk, dust, oil or wax residue cleaned off.

APPLICATION:

Allow the product to reach 20 °C before use. Apply evenly to the sub-floor with a roller or brush. Avoid piling on too much product when applying. Before bonding with our bicomponent or silane adhesives, always check the moisture content of the screed as, due to its water-based formula, ADEPROMOT-SPECIAL can increase the level of moisture. Optimum conditions for application are: Ambient temperature between 15 °C to 25 °C, relative humidity no greater than 75%. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

NOTES:

ADEPROMOT-SPECIAL can also be used as an adhesion promoter for applications with PAVILAST R (on absorbent surfaces) or ADECEM FIBER (on absorbent and non-absorbent surfaces).

HAZARD PICTOGRAMS:

-- -- --