



DILUENTE MB

RETARDER THINNER FOR SOLVENT-BASED VARNISHES

Retarder solution for solvent-based varnishes. DILUENTE MB is particularly recommended for very dry, warm environments. The product reduces the likelihood of blotches or overlaps when coating.

TECHNICAL CHARACTERISTICS:

- Slows varnish drying times considerably
- Suitable for summer weather conditions
- Compatible with all Adesiv solvent-based varnishes
- Recommended thinning: max 3-5%

WHERE THE VARNISH WITH ADDED DILUENTE MB THINNER CAN BE APPLIED:

- Warm rooms or other areas during summer
- Large surfaces
- On particularly absorbent wood

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Transparent liquid
Viscosity, Ford 4 at 20 °C (seconds):	11 - 12
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	5-litre containers
Usage limitations:	Flammable product Always use suitable personal protective equipment Always consult the technical and safety information sheets

APPLICATION:

After catalysis, add a maximum of 5 % of DILUENTE MB to a solvent-based varnish and mix thoroughly before use. Apply the paint or varnish in accordance with the product technical data sheet. Always consult the product's technical and safety information sheets before use.

HAZARD PICTOGRAMS:

