

NEW PAVIDEK



SEALER

Solvent-based sealer for treating and protecting outdoor wooden decking.

TECHNICAL CHARACTERISTICS:

- Excellent resistance outdoors
- Colourless
- Quick drying
- High penetration
- Slight toning effect

WHERE IT CAN BE APPLIED:

- Outdoor paving
- Wooden terraces
- Wooden beams and matchboarding
- Gazebos
- Swimming pool edges

DO NOT USE:

- Non-wooden surfaces
- Non-absorbent surfaces

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Amber-coloured liquid
Brookfield viscosity at 20 °C (mPa*s):	700 - 1000
Yield (l/m ²):	European/Asian wood: 10 – 15 South American wood: 25 – 30
Surface drying time (hours):	1-3
Final drying time (hours):	24 - 48
Usage temperature (°C):	+10 - +30
Application/Equipment:	Roller, brush
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	Packaging: 5-L
Usage limitations:	Flammable Do not apply to damp wood Do not use on non-absorbent floors Always use suitable personal protective equipment Always consult the technical and safety information sheets

SURFACE PREPARATION:

The wooden surface being treated must be sanded with 100/120 grit paper. In the case of South American wood, or when a non-slip surface is required, it is advisable to sand with 80/100 grit paper.

Alternatively, treat beforehand with NEW DECK (see technical data sheet) on dirty or greying surfaces. Before applying, clean the wooden surface thoroughly and ensure it is free from dust or loose parts.

APPLICATION:

Product ready to use. Apply a coat of Pavidek evenly over the surface using a brush. Apply a second coat of the product after 8-12 hours if necessary. Excessive amounts of product could make it more difficult to dry. Do not use on damp or wet surfaces or under direct exposure to sunlight, therefore avoid the warmest time of day. If using indoors ventilate the area. To ensure the best result it is advisable to protect the surface from rain in the 24 hours following treatment. Our OLIOPRO detergent (see technical data sheet) can be used for routine surface maintenance. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

HAZARD PICTOGRAMS:

