



PUREDEK

WATER-BASED SEALER

Water-based, non-film-forming sealer for treating and protecting outdoor wooden floors, swimming pool edges, outdoor furniture, piers and docks.

TECHNICAL CHARACTERISTICS:

- Excellent weather resistance
- Pigmented, it provides a slight toning effect
- Contains special UV absorbers
- Quick drying

WHERE IT CAN BE APPLIED:

- Outdoor paving
- Gazebos and garden furniture
- Swimming pool edges
- Docks and platforms

DO NOT USE:

- Non-wooden surfaces
- Non-absorbent surfaces

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Pigmented liquid
Colour:	Teak
Viscosity, Ford 4 at 20 °C (seconds):	30 - 36
Yield: (g/m ²):	70 - 100
Surface drying time (minutes):	60
Can be varnished over (hours):	2 - 4
Sanding time (hours):	12 - 16
Final drying time (hours):	24 - 48
Usage temperature (°C):	+10 - +30
Application/Equipment:	Roller, brush or spray bottle
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	5 L
Usage limitations:	Do not apply at hottest times of the day Do not apply to damp wood or non-absorbent surfaces Always use suitable personal protective equipment Always consult the technical and safety information sheets

SURFACE PREPARATION:

The wooden surface being treated must be sanded with 150/180 grit paper.

For dirty or greying surfaces, you can pre-treat with NEW DECK (see technical data sheet). Before applying, clean the wood surface thoroughly and ensure it is free from dust, loose parts or humidity.

APPLICATION:

Product ready to use. Apply a coat of PUREDEK evenly over the surface using a roller, brush or spray bottle. Apply a second coat of the product after 2 - 4 hours if necessary. If you wish to sand the surface between one coat and the next, wait around 12 - 16 hours after applying the first. Excessive amounts of product could make it more difficult to dry. Do not use on damp or wet surfaces or under direct exposure to sunlight, therefore avoid the warmest time of day. If using indoors ventilate the area. To ensure the best result, you should protect the surface from rain for 24 hours after it has been treated. Our OLIOPRO detergent (see technical data sheet) can be used for routine surface maintenance. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

HAZARD PICTOGRAMS:

