

## STONE



### MONOCOMPONENT POLYURETHANE VARNISH WITH NATURAL EFFECT

Water-based varnish with ultra-matte natural finish, which provides outstanding resistance to wear from high foot traffic. Nanotechnology-powered product.

#### TECHNICAL CHARACTERISTICS:

- Monocomponent
- Solvent-free
- Extremely resistant to foot traffic
- Easy to apply
- High coverage
- **Ultra-matte natural finish**

#### WHERE IT CAN BE APPLIED:

- Wood flooring
- Wooden surfaces in general (furniture, staircases etc.)

#### SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Milky liquid
Viscosity, Ford 4 at 20 °C (seconds):	29 - 34
Gloss value at 60°:	Ultra-matte 3 - 5
Yield: (g/m <sup>2</sup> ):	90 - 100 (the yield of the product may vary depending on the porosity or flatness of the surface being treated)
Dry dust free (minutes):	60 - 70
Sanding (hours):	8 - 12
Final setting (days):	2 - 5
Usage temperature (°C):	+ 15 - +25
Application/Equipment:	Roller, brush
Equipment cleaning:	Water, before the product sets
Product removal:	Water, before the product sets
Storage (months): temperature between +5 °C and +25 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	10 L kits (containers of 5 litres each)
Note:	Stir well before use
Usage limitations:	Frost sensitive. Do not apply in damp environments, avoid draughts and bring product up to room temperature before use Always use suitable personal protective equipment Always consult the technical and safety information sheets

**SURFACE PREPARATION:** The wood floor must be perfectly smooth, filled and sanded, free from loose parts that may interfere with adhesion (e.g. oil, wax, silicone). The surface to be finished must be dry, with 8 to 12% moisture content. Ambient temperature between 15 °C to 25 °C, relative humidity no greater than 75%. After sanding with 120/150 grit, vacuum the whole surface and then clean with an anti-static cloth.

**APPLICATION:** Leave the product to reach room temperature and stir carefully before use. Wait approximately 10–15 minutes, filter the product and apply an even coat using a roller or brush.

Always consult the product data sheet to ensure compatibility of coating systems.

CONTINUE



## STONE

### **MODERATE – HIGH TRAFFIC SYSTEM: PU 1 BASIC + 2 COATS OF STONE VARNISH (ultra-matte natural finish)**

**APPLICATION:** Leave the product to reach room temperature and stir carefully before use. Apply the first coat of the PU 1 BASIC primer evenly using a roller or brush. After approximately 8-12 hours in normal conditions, sand using 180 - 220 grit, clean the surface and apply a coat of STONE monocomponent varnish. If necessary, after approximately 8-12 hours, sand using 220 grit, clean the surface and apply a second coat of STONE monocomponent varnish. Always wear protective gloves. Always consult the technical and safety data sheet for the product.

#### **HAZARD PICTOGRAMS:**

-- -- --