



WPC OIL-WACHS

WPC PROTECTION

Wax and oil-based treatment for protecting composite materials such as WPC. Enhanced with UV filters, it provides excellent protection against stains and atmospheric agents.

TECHNICAL CHARACTERISTICS:

- Monocomponent
- Water-based
- Quick drying
- Excellent protection
- Contains UV filters

DO NOT USE:

- Non-WPC surfaces
- Non-absorbent surfaces

WHERE IT CAN BE APPLIED:

- WPC external flooring and coverings
- WPC swimming pool edges
- WPC docks and platforms
- Wooden surfaces (after a patch test)

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Opalescent liquid
Finish:	Matte
Viscosity, Ford 4 at 20°C (seconds):	10 – 12
Yield: (g/m ²):	16 - 20
Surface drying time (hours):	2 - 4
Final drying time (hours):	24 - 30
Usage temperature (°C):	+10 - +30
Application/Equipment:	Roller, brush or spray bottle
Storage (months): temperature between +5°C and +25°C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	5 L
Usage limitations:	Do not apply at hottest times of the day Do not apply to damp wood or non-absorbent surfaces Always use suitable personal protective equipment Always consult the technical and safety information sheets

SURFACE PREPARATION:

The surface to be treated must be clean, dry and grease- or silicone-free.

APPLICATION:

Thoroughly mix the product before use. Evenly apply a surface coat of WPC OIL-WACHS with a roller or brush. After approximately 6-8 hours, apply a second coat of the product. If you wish to sand the surface between one coat and the next, wait around 8 - 12 hours after applying the first. Excessive amounts of product could make it more difficult to dry. Do not use on damp or wet surfaces or under direct exposure to sunlight, therefore avoid the warmest time of day. If using indoors ventilate the area. To ensure the best result, you should protect the surface from rain for 24 hours after it has been treated. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

HAZARD PICTOGRAMS:

